

Stethoscopes - Comparison table

COMPARISON TABLE

Designation	TKST 11	TKST 21
Frequency range	30 Hz – 15 kHz	30 Hz – 15 kHz
Operating temperature	-10 to +45 °C (14 to 113 °F)	-10 to +45 °C (14 - 113 °F)
Output volume	Adjustable in 15 levels	Adjustable in 10 levels
Display	Black and white display	Colour backlit TFT
Sound volume	Up and down	Up, Down and mute
Battery low signal	Yes	Yes
Menus and features	Volume up, down and mute	Live, Recordings, Volume control, SKF sounds samples, Settings
Maximum recorder output	250 mV	250 mV
Headset with ear defender	32 Ohm (right and left merged)	32 Ohm (right and left merged)
Auto switch off	Yes, after 5 min.	After 5 or 10 min. or OFF
Battery	2 × AA Alkaline (included)	2 × AA Alkaline (included)
Battery lifetime	30 hours minimum	10 hours minimum (continuous use)
Dimensions handset	230 x 70 x 38 mm (9 x 2.8 x 1.5 in.)	230 x 70 x 38 mm (9 x 2.8 x 1.5 in.)
Probe length	70 and 300 mm (2.8 and 11.8 in.)	70 and 300 mm (2.8 and 11.8 in.)
Case dimensions	360 × 110 × 260 mm (14.2 × 4.3 × 10.2 in.)	360 × 110 × 260 mm (14.2 × 4.3 × 10.2 in.)
Weight		
- Total weight	1670 g (3.68 lb)	1 670 g (3.68 lb)
- Instrument	290 g (0.64 lb)	290 g (0.64 lb)
- Headset	290 g (0.64 lb)	290 g (0.64 lb)
Case contents	1 × Instrument 1 × Headset 1 × Probe 70 mm (2.8 in.) 1 × Probe 300 mm (11.8 in.) 2 × AA Alkaline battery 1 × Instructions for use	1 × Instrument 1 × Headset 1 × Probe 70 mm (2.8 in.) 1 × Probe 300 mm (11.8 in.) 2 × AA Alkaline battery 1 × Instructions for use